

Material Safety Data Sheet

Product Identification

Date: 10-19-2014

Product name: TITANIUM DIOXIDE
Synonyms: Titanium (IV) Oxide;
CAS No.: 13463-67-7
Molecular Weight: 79.87
Chemical Formula: TiO₂
Company: Shanghai Yihe New Materials Co.,Ltd
Add: Room911 No39 Changqing Road 1200 Nong,Shanghai,China
Tel: +86 021-2206 5797 Fax:+86 021-58383927

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
A-05 Titanium Dioxide	13463-67-7	99%	no

3. Hazards Identification

Emergency Overview

CAUTION! RESPIRATORY TRACT. MAY AFFECT LUNGS.

Flammability Rating: 0 - None
Reactivity Rating: 0 - None
Skin Contact Rating: 0 - None
Lab Protective Equip: GOGGLES; LAB COAT
Potential Health Effects: -----

Inhalation: May cause mild irritation to the respiratory tract.
Ingestion: Not expected to be a health hazard via ingestion.
Skin Contact: No harmful to skin
Eye Contact: May cause mild irritation, possible reddening.
Chronic Exposure: Long-term exposure to titanium dioxide dust may result in mild fibrosis (scarring of the lungs).

Aggravation of Pre-existing Conditions:
Persons with pre-existing lung disease may be more susceptible to the effects of this substance.

4. First Aid Measures

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty.
Ingestion: Not expected to require first aid measures. If large amounts were swallowed, give water to drink and get medical advice.
Skin Contact: Not expected to require first aid measures. flush skin with water

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Titanium Dioxide:

- OSHA Permissible Exposure Limit (PEL) - 15 mg/m³ (TWA).

- ACGIH Threshold Limit Value (TLV) -

- 10 mg/m³ (TWA), A4 - Not classifiable as a human carcinogen.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, a half-face dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece dust/mist respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not

known, use a full-facepiece positive-pressure, air-supplied respirator.

WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear appropriate gloves and clean body-covering clothing.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Free flowing white Powder.

Average size (nm): 5

Odor: Odorless.

Solubility: Insoluble in water.

Bulk density: 0.3 g/cm³

pH: ca. 6 - 8

% Volatiles by volume @ 21C (70F): 0

Boiling Point: 2500 - 3000C (4532 - 5432F)

Melting Point: 1855C (3371F)

Vapor Density (Air=1): Not applicable.

Vapor Pressure (mm Hg): Not applicable.

Evaporation Rate (BuAc=1): No information found.

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: No information found.

Hazardous Polymerization: Will not occur.

Incompatibilities:

For Titanium Dioxide: A violent reaction with lithium occurs around 200C (392F) with a flash of light; the temperature can reach 900C. Violent or incandescent reaction may also occur with other metals such as aluminum, calcium, magnesium, potassium, sodium, and zinc.

Conditions to Avoid: Dusting and incompatibles.

11. Toxicological Information

May be harmful or act as an irritant. Typical TLV/TWA 10 mg/m³.

No LD50/LC50 information found relating to normal routes of occupational exposure.

12. Other Information

Flammability: 0 Reactivity: 0

Label Hazard Warning:

CAUTION! MAY CAUSE IRRITATION TO EYES, AND RESPIRATORY TRACT. MAY AFFECT LUNGS.

Label Precautions: Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Avoid breathing dust.

Keep container closed.

Use with adequate ventilation.

Label First Aid:

In case of contact, flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. If inhaled, remove to fresh air. Get medical attention for any breathing difficulty.

Product Use: UV screen in cosmetic