

TECHNICAL DATA SHEET

INTRODUCTION :

NV-406 is a compound PE wax ,good lubricity and dispersancy ,high whiteness and stability .

NV-406W is cosmetic grade wax ,specially used in cosmetic products

PROPERTIES	PE WAX NV-406		
	UNIT	DATA	TEST METHOD
Appearance	WHITHE POWDER		
Viscosity(@140°C)	CPS	MAX 100	BROOKFIELD
Softening Point	°C	105±3	ASTM
Density	g/cm ³	0.93	ASTM
Penetration(@25°C)	d-mm	5	ASTM
TG	%	1.5	CONSTANT TEMPERATURE
Particle Size	%	99	20 MESH THROUGH

APPLICATION:

NOVO® POLYETHYLENE WAX	PE Wax NV-406
Masterbatch/色母粒	**
Filler Masterbatch/填充母料	**
PVC	*
Cabel Filler/电缆填充	*
Hot Melt Adhesive/热熔胶	*
Thermoplastic Road Marking/热塑性路标	**
Candle/蜡烛	*
Rubber/橡胶	*

* suitable

** recommend

PACKAGE: 25KG/BAG

SAFETY INSTRUCTIONS: Please refer to SDS for more information

For more information ,please visit : www.chemnovo.com.cn