

## TECHNICAL DATA SHEET

### INTRODUCTION :

NV-100 has low viscosity ,rather good lubricity,can be used in most kinds of plastic processing ,specially suitable to use in masterbatch,PVC and PVC stabilizer,hot melt adhesive and rubber .

PROPERTIES	PE WAX NV-100		
	UNIT	DATA	TEST METHOD
Appearance	WHITHE POWDER		
Viscosity(@140°C)	CPS	MAX 100	BROOKFIELD
Softening Point	°C	103±5	ASTM
Density	g/cm <sup>3</sup>	0.92	ASTM
Penetration(@25°C )	d-mm	8	ASTM
TG	%	2	CONSTANT TEMPERATURE
Particle Size	%	99	20 MESH THROUGH

### APPLICATION:

NOVO® POLYETHYLENE WAX	PE WAX NV-100
Masterbatch/色母粒	**
Filler Masterbatch/填充母料	*
PVC	**
Cable Filler/电缆填充	*
Hot Melt Adhesive/热熔胶	*
Thermoplastic Road Marking/热塑性路标	*
Candle/蜡烛	*
Rubber/橡胶	**

\* suitable

\*\* recommend

**PACKAGE:** 25KG/BAG

**SAFETY INSTRUCTIONS:** Please refer to SDS for more information

For more information ,please visit : [www.chemnovo.com.cn](http://www.chemnovo.com.cn)