

TECHNICAL DATA SHEET

INTRODUCTION :

NV-201 has high viscosity ,it is suitable to use in where high viscosity is demanded.

PROPERTIES	PE WAX NV-201		
	UNIT	DATA	TEST METHOD
Appearance	WHITHE POWDER		
Viscosity(@140°C)	CPS	1000±50	BROOKFIELD
Softening Point	°C	110±5	ASTM
Density	g/cm ³	0.93	ASTM
Penetration(@25°C)	d-mm	2	ASTM
TG	%	1	CONSTANT TEMPERATURE
Particle Size	%	99	20 MESH THROUGH

APPLICATION:

NOVO® POLYETHYLENE WAX	201	201H	202	208
Masterbatch/色母粒	*	*	*	**
Filler Masterbatch/填充母料	**	**	**	**
PVC	**	**	**	*
Cable Filler/电缆填充	*	*	*	*
Hot Melt Adhesive/热熔胶	**	**	**	*
Thermoplastic Road Marking/热塑性路标	**	**	**	**
Candle/蜡烛	**	**	**	**
Rubber/橡胶	*	*	*	**

* suitable

** recommend

PACKAGE: 25KG/BAG

SAFETY INSTRUCTIONS: Please refer to SDS for more information

For more information ,please visit : www.chemnovo.com.cn