

## TECHNICAL DATA SHEET

### INTRODUCTION :

NV-201H is a kind of heat cracked PE wax with high melting point and viscosity .Disperancy is good ,high whiteness ,specially suitable to use in where high melting point is required such as high melting point hot melt adhersive and engineering plastic(replace EBS)

PROPERTIES	PE WAX NV-201H		
	UNIT	DATA	TEST METHOD
Appearance	WHITHE POWDER		
Viscosity(@140°C)	CPS	800±50	BROOKFIELD
Softening Point	°C	120±3	ASTM
Density	g/cm <sup>3</sup>	0.93	ASTM
Penetration(@25°C )	d-mm	3	ASTM
TG	%	1	CONSTANT TEMPERATURE
Particle Size	%	99	20 MESH THROUGH

### APPLICATION:

NOVO® POLYETHYLENE WAX	201H	201	202	208
Masterbatch/色母粒	*	*	*	**
Filler Masterbatch/填充母料	**	**	**	**
PVC	**	**	**	*
Cable Filler/电缆填充	*	*	*	*
Hot Melt Adhesive/热熔胶	**	**	**	*
Thermoplastic Road Marking/热塑性路标	**	**	**	**
Candle/蜡烛	**	**	**	**
Rubber/橡胶	*	*	*	**

\* suitable

\*\* recommend

**PACKAGE:** 25KG/BAG

**SAFETY INSTRUCTIONS:** Please refer to SDS for more information

**For more information ,please visit : [www.chemnovo.com.cn](http://www.chemnovo.com.cn)**